



Stripping, Scrubbing, Resurfacing

The HAWK Pro is designed for the professional in mind. This severe duty machine handles the range of tasks with the 180-frame TEFC motor with hardened steel gears that drive rotary tools at 165 RPM

The Pro includes two removable 25 lb. weights mounted on the brush cover, a convenient upper handle lock, 3" wider handle, a 4 gallon, no-spill solution tank, pad driver and splash guard.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power. 50 ft. (12-3) SJTOW industrial power cord. 75 ft. (12-3) and 100 ft. (12-3) 2 piece cord available.

Drive System

- Triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler, drive brushes and pads at 165 RPM

Engineered Design

- All steel construction with welded, powder-coated frame
- One piece chrome, heavy-duty, extra wide ergonomic handle
- 13", 15", 17" and 20" brush covers with wraparound bumper
- Dual steel operating triggers. Thumb operated safety switch.
- Negative pressure on/off switch
- 1" x 5" non-marking ball bearing wheels
- Includes premium pad driver, 4 gallon solution tank and splash guard in private label colors
- Includes removable 80# weight set with mounting lock pins for extra down pressure and faster results

Safety Features

- Quiet 60 dB operation. Meets GS42 standard.
- UL/CUL listed

Accessories

- Dust pickup, surface prep scraper, Orbitec diamond pad driver, weighted diamond pad driver brushes, pads and drivers, sandpaper drivers. Details and part numbers pages 38-39.



Specifications

Model #	HP1513-180PRO	HP1515-180PRO	HP1517-180PRO	HP1520-180PRO
Part Number	F0013-180PRO	F0006-180PRO	F0009-180PRO	F0012-180PRO
Machine Size	13 inch	15 inch	17 inch	20 inch
Pad Size	12 inch	14 inch	16 inch	19 inch
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	7.2 Amp	7.5 Amp	7.9 Amp	8.4 Amp

All Sizes	
Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power	115-230V, 60 Hz power
Power Cord	50 ft. 12-3 SJTOW industrial power cord w/molded plug
Drive System	Triple-planetary XHD 11:1 helical-cut industrial gears
dB Rating	60 dB - Meets GS42 standard

Subject to Change Without Notice



Power to Drive Optional Orbitec Tools at 165 RPM



Includes Pad Driver & Splash Guard



Permanently Lubricated 11:1 Triple-Planetary Gears



Upper Handle Lock is Easy to Access