



Stripping, Sanding, Carpet Care, Resurfacing



The HAWK Osprey is the all surface restoration machine for vinyl, stone, wood, concrete, ceramic tile and carpet. A 45 PSI solution pump, 4.5 gallon solution tank and the adjustable 60 degree spray nozzle control the precise amount of cleaning solution to the floor. The 1.5 HP, 180-frame TEFC motor delivers plenty of power for the largest jobs.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power. 50 ft. (12-3) SJTOW cord with molded plug

Drive System

- Triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler, drives brushes and pads at 165 RPM

Engineered Design

- All steel construction with welded, powder-coated frame
- One piece chrome, heavy-duty steel handle with variable position lock and vinyl grips
- 13", 15", 17" and 20" brush covers with 360 degree bumper
- The 45 PSI solution pump is powered by the machine motor and controlled by the conveniently mounted handle switch
- A handle-mounted 4 gallon solution tank feeds the pump
- The solution spray valve on the pump delivers liquids to the floor at 0.25 gallon per minute
- Dual steel operating triggers. Negative pressure on/off switch.
- Thumb-operated safety switch
- Includes tufted pad driver and splash guard
- 1" x 5" non-marking ball bearing wheels

Safety Features

- Quiet 66 dB operation. Meets GS42 standard. UL/CUL listed.

Accessories

- Dust pickup, 25 lb. frame weights, surface prep scrapers, Orbitec diamond pad drivers, weighted diamond pad drivers, brushes, pads and drivers, sandpaper drivers. Details and part numbers on pages 38-39.



Specifications

Model #	HP1513-180OSPNEY	HP1515-180OSPNEY	HP1517-180OSPNEY	HP1520-180OSPNEY
Part Number	F0013-OSPNEY	F0006-OSPNEY	F0009-OSPNEY	F0012-OSPNEY
Machine Size	13 inch	15 inch	17 inch	20 inch
Pad Size	12 inch	14 inch	16 inch	19 inch
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	7.2 Amp	7.5 Amp	7.9 Amp	8.4 Amp

All Sizes

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power	115-230V, 60 Hz power
Power Cord	50 ft., (12-3) SJTOW industrial power cord w/molded plug
Drive System	Triple-planetary XHD 11:1 helical-cut industrial gears
Solution Pump	45 psi solution pump mounted on motor
dB Rating	66 dB - Meets GS42 standard

Subject to Change Without Notice



Welded Steel Frame, Handle & Brush Covers



45 PSI switch activated pump and solution tank



Includes Pad Driver & Splash Guard



7 Private Brand Colors