



Stripping, Scrubbing, Carpet Maintenance



The new Hawk Glide delivers up to twice the performance and superior safety over traditional floor machines. Our unique "Floating Head" handle carriage design provides 100% contact with the floor. The WD™ "Wheels Down" design steers the Glide in forward and backward movement - unlike the side-to-side movements of traditional rotary machines. Easy to learn. Easy to use.

Power

- 1.5 HP, 66 frame, dual capacitor AC motor
- 115V, 60 Hz power, (230V optional)
- 50 ft., (14-3) STO power cord with molded plug

Drive System

- **Glide** uses triple-planetary HD 10:1 helical-cut commercial gears. Drives brushes and pads at 175 RPM.
- **Glide XHD** (Extra Heavy-Duty) uses triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler. Drives brushes and pads at 165 RPM.

Engineered Design

- Exclusive WD™ detachable handle carriage design
- All steel construction with welded frame
- Heavy-duty powder coated steel handle with 5-position pin lock and vinyl grips
- 17" and 20" metal brush cover. 360 degree wraparound bumper.
- Dual steel operating triggers
- Negative pressure on/off switch. Thumb-operated safety switch.
- 2" x 5" non-marking ball bearing wheels

Safety Features

- Quiet 66 dB operation. Meets GS42 standard.
- Built with UL approved components

Accessories

- Dust pickup Glide kit, splash guard, 4.5 gallon solution tank, surface prep scraper, Orbitec diamond pad driver, weighted diamond pad driver brushes, pads and drivers, sandpaper drivers. 7 private label colors. Details and part numbers on pages 38-39.



Specifications

Model	GLIDE 17	GLIDE 17XHD	GLIDE 20	GLIDE 20XHD
Part #	F0091-17	F0091-17XHD	F0091-20	F0012-20XHD
Machine Size	17"	17"	20"	20"
Pad Size	16"	16"	19"	19"
Pad Speed	175 RPM	165 RPM	175 RPM	165 RPM
Gear Box	10:1	11:1	10:1	11:1
Amp Draw	6.7 Amp	7.1 Amp	6.9 Amp	7.3 Amp

All Models

Motor	1.5 HP, 66 frame dual capacitor AC motor
Power	115V, 60 Hz power, (230V optional)
Power Cord	50 ft., (14-3) STO power cord with molded plug
dB Rating	66 dB - Meets GS42 standard

Subject to Change Without Notice




Optional Dust Control Ring
Connects to Tank Vac



Available with 45 PSI
Solution Sprayer



Glide XHD Has Chromed
Motor w/ 11:1 Gear Box



5-Position Pin Lock Handle.
All Steel Construction.