



Stripping, Scrubbing, Carpet Maintenance

The Hawk Glide 2-Speed delivers twice the performance and superior safety over traditional floor machines. Our unique "Floating Head" handle carriage design provides 100% contact with the floor while incorporating forward and backward movement - unlike the side-to-side swing of traditional rotary machines. Scrub at 175 RPM (Standard) or 165 RPM (XHD). Polish at 320 or 350 RPM.

Power

- 1.5 HP, 66 frame, rectified 2-speed AC motor.
- 115V, 60 Hz power, (230V optional). 50 ft. (14-3) SJT power cord
- Hi/Low speed switch is located on the motor

Drive System

- **Glide** uses triple-planetary HD 10:1 helical-cut commercial gears to drive pads at 175 or 350 RPM
- **Glide XHD** triple-planetary XHD 11:1 helical-cut industrial gears with case hardened steel coupler drives pads at 165 or 320 RPM

Engineered Design

- Exclusive WD™ detachable handle carriage design
- All steel construction with welded frame heavy-duty powder coated steel handle with 5-position pin lock and vinyl grips
- 17" and 20" steel brush covers with full wraparound bumper
- Dual steel operating triggers. Negative pressure on/off switch.
- Thumb-operated safety switch
- 2" x 5" non-marking ball bearing wheels

Safety Features

- Quiet 62 dB (low speed), 69 dB (high speed) operation. Meets GS42 standard.
- Built with UL Listed components

Accessories

- Dust pickup Glide kit, splash guard, 4.5 gallon solution tank, surface prep scraper, Orbitec diamond pad driver, weighted diamond pad drivers 5 brushes, pads and drivers, sandpaper drivers. Details and part numbers pages 38-39.



Specifications

Model	GLIDE 17-2S	GLIDE 17-2SXHD	GLIDE 20-2S	GLIDE 20-2SXHD
Part #	F0091-17-2S	F0091-17-2SXHD	F0091-20-2S	F0091-20-2SXHD
Machine Size	17"	17"	20"	20"
Pad Size	16"	16"	19"	19"
Pad Speed	175/350 RPM	165/320 RPM	175/350 RPM	165/320 RPM
Gear Box	10:1	11:1	10:1	11:1
Amp Draw (Low/High Speed)	8.5/9.1 Amp	8.5/9.1 Amp	9.2/9.6 Amp	9.2/9.6 Amp

All Models

Motor - Glide	66 frame, 1.5 HP rectified 2-speed AC motor
Power	115V, 60 Hz. (230V optional)
Power Cord	50 ft. 14-3 SJT industrial power cord w/molded plug
dB Rating	62 dB (low speed) - 69 dB (high speed) Meets GS42 standard



XHD Uses 11:1 Triple Planetary Gears



Optional Dust Control Ring Connects to Tank Vacuum



2-Speed Motor with Hi/Lo Switch



5-Position Pin Lock Handle All Steel Construction

Subject to Change Without Notice