



Dry Stripping, Scrubbing, Stripping

The TigerHawk 2014 revolutionary rectangular floating head is easy to maneuver with less vibration, noise and fatigue than other orbiting brands. The WD™ handle design assures 100% pad contact with the floor. The 2014 works three times faster than rotary floor machines, easily reaching into corners and along baseboards. Add a handle mounted vacuum tank for wet scrubbing. The TigerHawk 2014 can strip large areas of floor finish with or without chemicals. Use for sanding, scrubbing and stone stripping. Easy to learn. Easy to use.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft. 2-part (12-3) SJTOW industrial power cord with molded plug

Drive System

- Essentric balanced orbital drive works at 1725 RPM

Engineered Design

- Dual vibration isolation system
- The WD™ powder-coated, heavy-duty steel handle is easy to remove
- 5-position pin lock handle adjustment and vinyl grips
- Includes severe-duty motor guard - protects the motor from impact damage
- 2" x 8" non-marking ball bearing wheels.
- Thumb-operated safety switch. Dual steel operating triggers.
- Negative pressure on/off switch.
- 2014 drive plate is built with a vacuum port. The vacuum "V" model connects here with 6 quart tank vacuum and dust skirt.
- Spray "SP" model adds motor-mounted solution pump and handle-mounted 4.5 gallon solution tank

Safety Features

- Quiet 66 dB operation. Meets GS42 standard. UL/CUL listed.

Accessories

- Full wraparound dust skirt , 4.5 gallon solution tank, (4) abrasive strengths 20"x14" orbital pads and 4 pad starter kit, and 20"x14" abrasive screens. Details and part numbers on pages 40.



Specifications

Model	TH-2014	TH2014-SP	TH2014-V
Part Number	F-TIGER2014	F-TIGER 2014-SP	F-TIGER2014-V
Pad Size	20" x 14"	20" x 14"	20" x 14"
Configuration	Standard	w/ Solution Pump & 4.5 Gal. Solution Tank	w/ 6 Qt. Tank Vacuum & Skirt
Pad Speed	1725 RPM	1725 RPM	1725 RPM
Amp Draw	7.1 Amp	7.1 Amp	11.8 Amp
Weight	250 lbs.	259 lbs.	269 lbs.
Pad Pressure	0.89 lbs/in ²	0.92lbs/in ²	0.96 lbs/in ²

All Models

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power Source	115-230V, 60 Hz power
Power Cord	50 ft., 2-Part (12-3) SJTOW industrial power cord w/molded plug
Drive System	Essentric balanced orbital drive
Vibration Isolators	(6) primary, (8) secondary isolaters

Subject to Change Without Notice



Works Along Baseboards and Into Corners



TH2014-SP Model Adds the Spray Pump and Solution Tank



Steel Frame with Rear Vacuum Port



TH2014-V Model Adds the 6 Quart Tank Vac, Dust Skirt and Hoses