



Dry Floors, Circulate and Exhaust Air



BH20DT

BH20DT - 1/5 HP, 3-Speeds up to 800 CFM

The multipurpose BH20DT air mover is affordable, lightweight (10 lb.) and easy to transport. It fits easily into tight areas, crawl spaces, closets and hallways. Includes an auxiliary 12 Amp outlet for connecting multiple units in series. The 3-hour timer and speed control allows precise controlled operation

BH50 - 1/2 HP, 3-Speeds up to 2800 CFM

BH50 is the best choice for a lightweight and mobile air mover that does not compromise on power or performance.



BH50

With a 1/2 HP motor capable of up to 2,800 CFM and running at an energy efficient 5.0 Amps, this unit weighs less than 20 lbs. Four adjustable positioning angles allow the BH50 to dry carpets, floors, walls and large areas quickly and efficiently. Stackable and manufactured with rugged state-of-the-art injection mold technology.

Engineered Design

- Strong polypropylene chassis design allows multiple air movers to be stacked on top of another
- Molded-in handle for easy transport
- Direct airflow at 0, 15, 45 and 90 degrees
- The plastic cage protects motor and fans from debris
- Open air intake screens allow for maximum air output
- Model BH20DT includes a 12 Amp GFCI auxiliary power outlet
- Includes 10 ft. (BH20DT) and 20 ft. (BH50) power cord
- An optional transport cart is available for BH50 model



Specifications

Model	BH20DT	BH50
Motor 3 Speed	1/5 HP	1/2 HP
CFM	800 cfm	2,800 cfm
Amp Draw	2.3 Amp	5.0 Amp
Chassis	Injection Molded Polypropylene	
Auxiliary Power Outlet	12 Amp	No
3 Hour Timer	Yes	No
Thermal Protection	Yes	Yes
Power Cord	10 ft., (14-3) cord	20 ft., (16-3) cord
UL Listed	Yes	Yes
Unit Dimensions (L x W x H)	10.7" x 12.4" x 13.3	15.9" x 15.7" x 16.3"
Weight	9.9 lbs.	19 lbs.


Subject to Change Without Notice



12 Amp Aux. Power Outlet on BH20



BH20DT Moves More Air with Daisy Chained Power



Air Flow in 4 Angles



Optional Telescopic Transport Cart for BH50
BH50-WHLKT