



Stripping, Scrubbing, Polishing

Machine operators will appreciate the performance, versatility and value in the Hawk Mighty. The 1.0 HP TEFC AC motor and XHD gears deliver huge power in a small and manageable machine. It's ideal for use in tight spaces, restrooms, edging and stairs. The "TH" models with Telescoping Handle fit every operator's height, and store in tight spaces.

Power

- 1.0 HP, 56 frame, dual capacitor, AC motor
- 115-230V , 50/60 Hz power. 50 ft. 14-3 SJT power cord.

Drive System

- Triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler. Drives brushes at 165 RPM.

Engineered Design

- All steel construction with welded, powder-coated frame
- Telescoping handle (TH models) adjusts from 36" to 48"
- 13" and 15" brush covers have full wraparound bumper
- One piece powder-coated, heavy duty steel handle with 5-position pin lock
- Comfortable vinyl handle grips
- Thumb-operated safety switch
- Negative pressure on/off switch
- Dual steel operating triggers
- 1"x5" non-marking ball-bearing wheels

Safety Features

- Quiet 64 dB operation. Meets GS42 standard.
- Built with UL Listed components

Accessories

- 13" and 15" splash guard, 2.5 gallon solution tank, 4 rotary brushes, diamond pad drivers, weighted diamond pad drivers, standard pads, drivers and hardware. Details and part numbers pages 38-39.



Specifications

Model	MIGHTY13	MIGHTY 13-TH	MIGHTY15	MIGHTY15-TH
Part #	F0060-13	F0060-13TH	F0060-15	F0060-15TH
Size	13"	13"	15"	15"
Pad Size	12"	12"	14"	14"
Telescoping Handle	No	Yes	No	Yes
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	4.9 Amp	4.9 Amp	6 Amp	6 Amp
Weight	87 lbs.	87 lbs.	88 lbs.	88 lbs.

All Models

Motor	1.0 HP, 56 frame, dual capacitor AC motor
Power Source	115-230V, 50/60 Hz power
Power Cord	50 ft. 14-3 SJT power cord w/molded plug
Driver System	Triple-planetary XHD 11:1 helical-cut industrial gears
dB Rating	64 dB - Meets GS42 standard

Subject to Change Without Notice



Works in Tight Spaces



Telescoping Handle Adjusts from 36" to 48"



Optional 2.5-Gallon Solution Tank



Handle with 6-Position Pin Lock