



Stripping, Scrubbing, Carpet Care

Realize maximum power with the twin capacitor, AC motor and Hawk's ruggedly reliable floor machine design. Machine operators appreciate the solid performance of an extremely well-built floor machine that delivers reliability on every job they tackle.

Power

- 1.5 HP, 66 frame, dual capacitor AC motor
- 115V, 60 Hz power, (230V optional)
- 50 ft. (12-3), 2-piece power cord with molded plug. 75 ft. (12-3) and 100 ft. (12-3) power cord available.

Drive System

- Triple-planetary HD 10:1 helical-cut commercial gears drive pads and brushes at 175 RPM

Engineered Design

- All steel construction with welded, powder-coated frame
- One piece chrome, heavy-duty steel handle with vinyl grips
- Variable position positive handle lock
- 13", 15", 17" and 20" brush covers with 360 degree wraparound bumper
- Dual steel operating triggers
- Negative pressure on/off switch
- Thumb-operated safety switch
- 1" x 5" non-marking ball-bearing wheels

Safety Features

- Quiet 60 dB operation. Meets GS42 standard.
- UL/CUL listed

Accessories

- Dust pickup, splash guard, hexagonal weights, 20 lb. frame weights, 4 gallon solution tank, brushes, pads and drivers, sandpaper drivers
- Details and part numbers on pages 38-39.



Specifications

Model #	HP1513-HD	HP1515-HD	HP1517-HD	HP1520-HD
Part #	F0013	F0006	F0009	F0012
Machine Size	13 inch	15 inch	17 inch	20 inch
Pad Size	12 inch	14 inch	16 inch	19 inch
Pad Speed	175 RPM	175 RPM	175 RPM	175 RPM
Current Draw	5.3 Amp	5.7 Amp	5.9 Amp	6.5 Amp

All Models

Motor	1.5 HP, 66 frame, dual capacitor AC motor
Power	115V, 60 Hz power, (230V optional)
Power Cord	50 ft. 12-3 two-piece power cord with molded plug
Drive System	Triple-planetary HD 10:1 helical-cut commercial gears
dB Rating	60 dB - Meets GS42 standard

Subject to Change Without Notice



Welded Steel Frame and Handle



Permanently Lubricated Triple Planetary Gears



DX Model Includes Chrome Motor, Splash Guard & Pad Driver



7 Private Brand Colors Plus Chrome