



Stripping, Buffing, Carpet Care

The Hawk 2-Speed floor machine performs heavy-duty scrubbing and stripping at the standard 175 RPM speed. With the flip of the conveniently located toggle switch, buff and polish at 320 RPM.

Power

- 1.5 HP, 66 frame, DC rectified 2-speed motor
- 115V, 60 Hz power, (230V optional)
- 50 ft., (14-3) STO industrial power cord with molded plug
- Change speed with Hi-Lo speed control switch on handle

Drive System

- Triple-planetary HD 10:1 helical-cut commercial gears drive pads/brushes at 175 or 320 RPM

Engineered Design

- All steel construction with welded, powder-coated frame
- One piece chrome, heavy-duty steel handle with variable position lock and vinyl grips
- 13", 15", 17" and 20" brush covers with 360 degree wraparound bumper
- Dual steel operating triggers
- Negative pressure on/off switch
- Thumb-operated safety switch
- 1" x 5" non-marking ball bearing wheels

Safety Features

- Quiet operation – 62 dB (low speed), 69 dB (high speed). Meets GS42 standard.
- UL/CUL listed

Accessories

- Dust pickup, splash guard, hexagonal weights, 20 lb. frame weights, 4 gallon solution tank, brushes, pads and drivers, sandpaper drivers. Details and part numbers pages 38-39.



Specifications

Model #	HP1513-2S	HP1515-2S	HP1517-2S	HP1520-2S
Part #	F0003-13	F0003-15	F0003-17	F0003-20
Machine Size	13 inch	15 inch	17 inch	20 inch
Pad Size	12 inch	14 inch	16 inch	19 inch
Pad Speed RPM	175/320 RPM	175/320 RPM	175/320 RPM	175/320 RPM
Amp Draw	7.8/8.2 Amp	8.1/8.5 Amp	8.5/9.1 Amp	9.2/9.5 Amp

All Sizes	
Motor	1.5 HP, 66 frame, DC rectified 2-speed motor
Power	115V, 60 Hz power, (230V optional)
Power Cord	50 ft. (14-3) STO industrial power cord w/molded plug
Drive System	Triple-planetary HD 10:1 helical-cut commercial gears
dB Rating	62dB (175 RPM) - 69dB (320 RPM) - Meets GS42 standard

Subject to Change Without Notice



Hi/Lo Speed Motor Switch on Handle



7 Private Brand Color Brush Covers



Optional 4 Gallon Solution Tank



1.5 HP Power to Drive the Range of Brushes