



Dry Floors, Circulate and Exhaust Air

The Hawk BVP50 is the safest and most efficient centrifugal air mover on the market. Our 1/2 HP motor powers an airflow up to 2820 CFM with just 4.5 amps usage.

Control the air flow and amp draw with our state of the art 2-speed moisture resistant switch. The rotationally molded body is strong, lightweight and easy to transport, clean and easy to stack. The BVP50H model adds a telescoping handle frame with transport wheels.

Engineered Design

- The 1/2 HP, 2-Speed motor is efficient and produces up to 2820 CFM airflow
- 25 ft. 16 AWG power cord
- The motor is sealed to prevent moisture from entering and damaging internal motor components
- The side-mounted 2-speed switch is moisture resistant
- Sturdy roto-molded plastic frame design has a profile that allows for vertical stacking up to 4 units for convenient storage
- The **BVP50** multipurpose design directs air at 3 angles (horizontally, 45° and 90°)
- The **BVP50H** adds a telescoping handle and transport wheels. Use horizontally, or tip back 90 degrees and move air straight upward.
- A plastic cage protects motor and fans from debris
- C-ETL listed
- 2 year warranty on parts. 5 year warranty on rotomolded chassis.



**HAWK BVP50
2820 CFM Air Mover**



**HAWK BVP50H
with Handle and
Transport Wheels**



Specifications

Model	BVP50, BVP50H (with Telescoping Handle & Wheels)
Motor	1/2 HP, 115V, 60Hz
Air Volume	2820 CFM (High Speed) / 2390 CFM (Low Speed)
Amp Draw	4.5 Amp (High Speed) / 2.8 Amp (Low Speed)
Max Static Pressure	2.5"
Air Flow Direction	0, 45 and 90 degrees
Frame Construction	Sturdy roto-molded plastic
Stackable	4 units
Weight	25 lbs. (net) / 28 lbs. (gross)
Size (LxWxH)	22.5"x 20"x 13"
Attached Cord	25 Ft. 16 AWG
Sound Level	74 dB
Certification	C-ETL-US

Subject to Change Without Notice



Store Up To
5 Stacked Units



BVP50H Adds Dual
Transport Wheels and
Telescoping Handle



Direct Airflow at 3 Angles
(Horizontally, 45° and 90°).



Compact Air
Moving Power