



Stripping, Scrubbing, Polishing

Machine operators will appreciate the performance, versatility and value in the HAWK Mighty. The 1.0 HP TEFC (Totally Enclosed Fan Cooled) AC motor and XHD gears deliver huge power in a small and manageable machine.

The Mighty is ideal for use in tight spaces, edging, and stairs. **Can be used in wet and dry applications with solution tank or dust control.**

The HAWK Mighty innovative design incorporates a state of the art "World Motor" works around the globe without modification.

Power

- 1.0 HP, TEFC AC Motor
- 115-230V, 50/60 Hz power
- 50 ft., (12-3) 2-piece commercial power cord with cord lock

Drive System

- Triple-planetary severe-duty 11:1 w/steel coupler
- Gears drive brushes and pads at 165 RPM

Engineered Design

- All steel construction with welded, powder-coated frame
- Telescoping handle (TH models) adjusts from 36" to 48"
- Brush covers have full wraparound bumper
- One piece powder-coated, heavy-duty steel handle with 6-position pin lock
- Comfortable vinyl dipped foam handle grips
- Thumb-operated safety switch
- Dual steel operating triggers
- 1" x 5" non-marking ball bearing wheels
- Optional dust collection kit (#A0803-13)
- Optional 4 gallon solution tank (#A0001-Color4)

Safety Features

- Quiet 64 dB operation. Meets GS42 standard.
- Built with UL Listed components



Optional
Cord
Wrap Hook

Mighty
w/ Telescoping
Handle

Mighty
w/ Rigid Handle



Specifications

Model	MIGHTY 13	MIGHTY 13-TH	MIGHTY 15	MIGHTY 15-TH
Item #	F60-13	F60-13TH	F60-15	F60-15TH
Handle	Rigid	Telescoping	Rigid	Telescoping
Size	13"	13"	15"	15"
Pad Size	12"	12"	14"	14"
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	4.9	4.9	6	6
Weight	87 lbs.	87 lbs.	88 lbs.	88 lbs.

All Models

Motor	1.0 HP, TEFC AC
Power Source	115-230V, 50/60 Hz
Power Cord	50 ft., (12-3) 2-piece commercial with cord lock
Gear Box	Triple-planetary XHD 11:1 helical-cut industrial
Sound Level (ave.)	64 dB - Meets GS42 standard


Subject to Change Without Notice



Works in
Tight Spaces



Telescoping Handle
Adjusts from 36" to 48"



Optional 2.5-Gallon
Solution Tank



Handle with 6-Position
Pin Lock